

Practical Hadoop By Example

Introduction: Moving Beyond Theory to Practical Hadoop By Example

For years, Apache Hadoop has stood as a cornerstone of the big data ecosystem. Countless articles, tutorials, and courses explain its architecture—the

Hadoop Distributed File System (HDFS), YARN for resource management, and MapReduce for processing. But there is a significant gap between understanding these concepts in theory and applying them to solve real-world problems. This is where the approach of **Practical Hadoop By Example** becomes invaluable. Instead of drowning in abstract definitions, learners and practitioners benefit

most by walking through concrete scenarios, from ingesting server logs to joining massive datasets. This article provides a hands-on journey through several practical Hadoop examples, illustrating how to move from raw data to meaningful insights using the Hadoop ecosystem.

Why Examples Matter in Learning Hadoop

Hadoop is not a single tool but a platform. It includes storage, processing, data ingestion, and

coordination services. Memorizing configuration parameters or the nuances of the `job.setNumReduceTasks()` method is far less effective than seeing how these pieces fit together in a real workflow.

Practical Hadoop By Example bridges the gap between documentation and application. When you work through an example—such as processing web server access logs to count page views per hour—you internalize how HDFS distributes data, how a MapReduce job splits work across nodes, and how the output lands back in a usable format. Examples also

reveal common pitfalls, such as data skew in reducers or slow HDFS writes, which are rarely covered in introductory theory.

Setting Up a Practical Hadoop Environment

Before diving into examples, it is essential to have a working Hadoop environment. While a full production cluster with dozens of nodes is impressive, most learning happens on a single-node setup or a small cluster in the cloud. For the examples in this article, a single-node

Hadoop installation in pseudo-distributed mode is sufficient. You can use a virtual machine image from Cloudera or Hortonworks (now part of Cloudera), or manually install Apache Hadoop on a Linux machine. Ensure HDFS is formatted and both the NameNode and DataNode are running, along with YARN's ResourceManager and NodeManager. Having the command-line tools `hdfs`, `dfs` and `yarn` accessible will allow you to follow along with the **Practical Hadoop By Example** exercises.

Ingesting and Querying Server Logs with HDFS

and Hive

The Scenario

Imagine you run an e-commerce website and collect access logs in the standard Apache Combined Log Format. Each line contains the client IP, timestamp, request method, URL, status code, and response size. Your goal is to answer a simple business question: "Which five product pages received the most visits in the last month?" This is a

perfect use case for a
Example 1:
Practical Hadoop By
Example
walkthrough.

Step 1: Ingest Data into HDFS

First, move your log files into HDFS. Assume your logs are stored locally in `/var/log/nginx/access.log`. Use the following command to create a directory and copy the file:

- **Create a directory:** `hdfs dfs -mkdir -p /user/yourname/logs`
- **Copy the file:** `hdfs dfs -put /var/log/nginx/access.log /user/yourname/logs/`

Practical Hadoop By Example

This places your data into a distributed storage system, making it available for processing across the cluster.

Step 2: Define a Hive Table

Apache Hive provides a SQL-like interface to data stored in HDFS. You can create an external table pointing to your log directory so that Hive does not move the data but reads it in place. Run the following HiveQL:

```
CREATE EXTERNAL
TABLE access_logs (
    ip STRING,
    timestamp
STRING,
    request STRING,
    status INT,
    size INT
```

```
)
ROW FORMAT SERDE
'org.apache.hadoop.
hive.serde2.RegexSe
rDe'
WITH
SERDEPROPERTIES (
    "input.regex" =
"^((\\S+) \\S+ \\S+
\\[(. *?)\\]
\"(. *?)\" (\\d{3})
(\\d+|-).*"
)
STORED AS TEXTFILE
LOCATION
'/user/yourname/log
s';
```

Notice the use of a regular expression to parse the log lines. This step shows how **Practical Hadoop By Example** forces you to deal with messy, real-world data formats.

Step 3: Run a Query

Now, you can answer the business question directly with a SQL query:

```
SELECT request,
COUNT(*) AS
hit_count
FROM access_logs
WHERE request LIKE
'/product/%'
GROUP BY request
ORDER BY hit_count
DESC
LIMIT 5;
```

This query filters for product page requests, counts occurrences, and returns the top five. Hive translates this into a MapReduce job that runs across your cluster. By completing this example, you

have used HDFS for storage and Hive for processing, illustrating a core **Practical Hadoop By Example** workflow.

Example 2: Building a Custom MapReduce Job for Data Aggregation

The Scenario

Suppose you have a dataset containing sales transactions with fields: transaction_id, customer_id, product_id, quantity, and price. You need to calculate the total revenue per

Practical Hadoop By Example

product. While Hive can do this, writing a custom MapReduce job gives you finer control over performance and logic. This is a classic **Practical Hadoop By Example** exercise for developers.

The Mapper

The mapper reads each line of the input, splits it by a delimiter (comma or tab), and emits the product ID as the key and the revenue (quantity * price) as the value.

```
public class
RevenueMapper
extends
Mapper<Object,
Text, Text,
DoubleWritable> {
    private Text
productKey = new
```

```
Text();
    private
DoubleWritable
revenueVal = new
DoubleWritable();

    public void
map(Object key,
Text value, Context
context) throws
IOException,
InterruptedException
n {
        String[]
fields =
value.toString().sp
lit(",");
        String
productId =
fields[2];
        int
quantity =
Integer.parseInt(fi
elds[3]);
        double
price =
Double.parseDouble(
fields[4]);
        double
```

```

revenue = quantity
* price;
productKey.set(prod
uctId);
revenueVal.set(reve
nue);
context.write(produ
ctKey, revenueVal);
    }
}

```

The Reducer

The reducer sums up the revenue values for each product.

```

public class
RevenueReducer
extends
Reducer<Text,
DoubleWritable,
Text,
DoubleWritable> {
    private
DoubleWritable
totalRevenue = new
DoubleWritable();

    public void

```

```

reduce(Text key,
Iterable<DoubleWrit
able> values,
Context context)
throws IOException,
InterruptedException
{
    double sum
= 0.0;
    for
(DoubleWritable val
: values) {
        sum +=
val.get();
    }
    totalRevenue.set(su
m);
    context.write(key,
totalRevenue);
}
}

```

The Driver

Finally, the driver class configures the job, sets input and output paths, and launches it on the

Practical Hadoop By Example

cluster. This example demonstrates the core MapReduce pattern: splitting data, processing in parallel, and aggregating results. By working through this code, you gain a deeper understanding of data flow in Hadoop, which is a key benefit of **Practical Hadoop By Example**.

Example 3: Joining Two Large Datasets with MapReduce

The Scenario

Joins are common in data analysis. Suppose you have a customers file with fields

customer_id and customer_name, and an orders file with order_id and customer_id. You want to produce a list of all orders with the corresponding customer name. Performing this join in a relational database is trivial, but with huge datasets, Hadoop shines. This **Practical Hadoop By Example** exercise shows you how to implement a reduce-side join.

The Map Phase

In the mapper, you read from both files. You need a way to distinguish records from the two datasets. Tag each record with a marker, for example,

"C" for customer and "O" for order. Emit the customer ID as the key and the tagged record as the value.

The Reduce Phase

In the reducer, all records for a given customer ID arrive together. You can buffer the customer name (the record with tag "C") and then for each order record (tag "O"), emit the order ID along with the customer name. This pattern is a classic **Practical Hadoop By Example** of solving distributed joins.

A key challenge here is memory: if a single customer has millions of orders, you might

run out of memory buffering them. A practical optimization is to ensure the smaller dataset is loaded into memory in the mapper (a map-side join), but that requires careful configuration.

Working through this example teaches you to think about data distribution and resource limits, which are critical in real-world systems.

Example 4: Using Apache Spark on Hadoop (The Modern Approach)

Practical Hadoop By Example

The Scenario

While MapReduce is foundational, many organizations now use Apache Spark for faster in-memory processing. Spark runs on top of HDFS and YARN, making it a natural extension of a Hadoop environment. In this **Practical Hadoop By Example**, you will process the same sales dataset from Example 2, but using Spark's DataFrame API in Python (PySpark).

Reading Data from HDFS

Assume your sales data is stored in HDFS at `/user/yourname/sales.csv`. The Spark code

is concise:

```
from pyspark.sql
import SparkSession

spark =
SparkSession.builder
r.appName("SalesAnalysis").getOrCreate
()
df =
spark.read.option("
header",
"false").csv("hdfs:
///user/yourname/sales.csv")
df =
df.toDF("transaction_id",
"customer_id",
"product_id",
"quantity",
"price")
```

Calculating Revenue Per Product

Now, add a revenue

column and
aggregate:

```
from  
pyspark.sql.functions import col  
  
df_with_revenue =  
df.withColumn("revenue",  
col("quantity") *  
col("price"))  
revenue_per_product =  
df_with_revenue.groupBy("product_id").  
sum("revenue")  
revenue_per_product.  
show()
```

This example shows how Spark simplifies code while still running on the same Hadoop infrastructure. It is a perfect **Practical Hadoop By Example** for teams transitioning from

MapReduce to Spark.

Best Practices Learned from Practical Hadoop Examples

Working through these examples reveals several best practices that are universally applicable:

- **Always test with small datasets first.** Before launching a job on terabytes of data, test with a sample of a few kilobytes. This saves time and debugging effort.

Practical Hadoop By Example

- **Monitor your jobs.** Use the YARN ResourceManager web UI or command-line tools to track progress and diagnose failures. Resource contention is a common issue.
- **Optimize data serialization.** Use sequence files, Avro, or Parquet instead of plain text. These formats are compressed, splittable, and faster to process.
- **Handle data skew.** In MapReduce joins, a key with very high frequency can

overload a single reducer.

Techniques like salted keys or combiners can mitigate this.

- **Document your workflow.**

Hadoop jobs are often run periodically.

Clear documentation of HDFS paths, table schemas, and job parameters ensures maintainability.

Common Pitfalls and How to Avoid Them

Even with **Practical Hadoop By Example**

at hand, beginners encounter common mistakes. One is forgetting to set the correct input format. If your data is not plain text but JSON or some custom binary format, you must configure the appropriate `InputFormat` class. Another frequent issue is the "small files problem" in HDFS: storing millions of small files puts